

Features & Benefits

Availability

N+1 REDUNDANCY:

The ability to add another power module provides N+1 redundancy and increases the availability of the solution

EXTENDABLE RUN TIME:

Additional batteries can be added to provide power to the load for an extended period of time in the event of utility supply failure.

BUILT-IN STATIC BYPASS SWITCH:

The built-in static bypass switch enables the UPS to transfer the load to utility power, without interruption, in case of heavy overload or faulty conditions.

Economy

FULL-RATED POWER WITH KVA EQUALING KW :

The full rated inverter of the Symmetra PX is a perfect match for today's power factor corrected computer loads, eliminating the need for an oversized UPS

TEMPERATURE COMPENSATED BATTERY CHARGING:

Temperature Compensated Battery Charging provides prolonged battery life by regulating the charge voltage according to actual battery temperature.

SCALABLE POWER CAPACITY:

The modular design of the Symmetra PX allows the user to add power modules as required. Thus the user will be able to deploy UPS protection in a "pay as you grow" approach.

Serviceability

AUTOMATIC SELF TEST :

The product automatically performs a self-test every two weeks. This ensures you will be alerted to degraded batteries before they wear out. Through software, or the push of a button, you may perform self-tests anytime.

HOT SWAP BATTERIES:

The modular battery design provides ease of maintenance and reduces Mean Time To Repair. A service engineer or trained user can easily swap a battery module in a matter of minutes while the UPS remains on-line.

MODULAR-LEVEL REPAIR :

The modular fault-tolerant design ensures system availability, until service can be performed, and reduces the risk of human errors.

FRONT-ACCESS SERVICING:

The front-access feature makes installation and maintenance easy and minimizes space requirements.

Manageability

BUILT-IN WEB/SNMP MANAGEMENT :

Provides full UPS management via multiple open standards like Telnet, HTTP, SNMP and pager notifications. It is a full-featured, robust power management product that is certified for and integrates with all other APC management products.

INTELLIGENT BATTERY MANAGEMENT :

The Symmetra PX features advanced battery monitoring and temperature-compensated battery charging. Battery data is continuously compared to pre-programmed data in the monitoring software to ensure reliable batteries. A reduction in battery capacity automatically triggers an alarm.

MULTIPLE SYSTEM SHUTDOWN:

Provides graceful, unattended shutdown for the connected servers should an extended power outage occur.

SMART SLOT:

By adding APC accessory cards into the SmartSlot you can monitor power conditions and take actions accordingly. The addition of the accessory cards increases overall system availability by proactively notifying you of conditions that could affect uptime (accessories sold separately).

Symmetra® PX 40kW

Scalable, redundant power protection for centralized IT equipment in medium to large data centers



Symmetra PX, three-phase input / three-phase output (3:3), is a single unit, composed of modular components. This modular architecture provides the foundation of building and scaling near-continuous availability power systems with a flexible range of power capacity. The Symmetra PX packages the high availability requirements of easy power and runtime scalability into a very small footprint. Combined with the complete line of APC data center protection software and accessories it provides the four most critical elements of total data center protection.

Technical Specifications	SY10K40F	SY20K40F	SY30K40F	SY40K40F
COMMUNICATION				
Interface port	Contact Closure, RJ-45 10 Base-T ethernet for web/ SNMP/ Telnet management, SmartSlot	RJ-45 10 Base-T ethernet for web/ SNMP/ Telnet management, SmartSlot	Contact Closure, RJ-45 10 Base-T ethernet for web/ SNMP/ Telnet management, SmartSlot	Contact Closure, RJ-45 10 Base-T ethernet for web/ SNMP/ Telnet management, SmartSlot
Emergency Power Off (EPO)	Yes	Yes	Yes	Yes
OUTPUT				
Output power capacity	10,000 VA	20,000 VA	30,000 VA	40,000 VA
Output power capacity	10,000 Watts	20,000 Watts	30,000 Watts	40,000 Watts
Max Configurable Power	40,000 VA	40,000 VA	40,000 VA	40,000 VA
Max Configurable Power	40,000 Watts	40,000 Watts	40,000 Watts	40,000 Watts
Nominal output voltage	120 (3PH), 208 (3PH) VA	120 (3PH), 208 (3PH) VA	120 (3PH), 208 (3PH) VA	120 (3PH), 208 (3PH) VA
Waveform type	Sinewave	Sinewave	Sinewave	Sinewave
Output Connections	(1)Hard Wire 5-wire (3PH + N + G), (1)Screw Terminals	(1)Hard Wire 5-wire (3PH + N + G), (1)Screw Terminals	(1)Hard Wire 5-wire (3PH + N + G), (1)Screw Terminals	(1)Hard Wire 5-wire (3PH + N + G), (1)Screw Terminals
INPUT				
Efficiency at full load	--	--	--	--
Bypass	Built-in Static Bypass	Built-in Static Bypass	Built-in Static Bypass	Built-in Static Bypass
Output Voltage Distortion	less than 5% at full load	less than 5% at full load	less than 5% at full load	less than 5% at full load
Output Frequency (sync to mains)	57-63Hz for 60Hz nominal	57-63Hz for 60Hz nominal	57-63Hz for 60Hz nominal	57-63Hz for 60Hz nominal
Crest Factor	Unlimited	Unlimited	Unlimited	Unlimited
Nominal input voltage	208 (3PH) V	208 (3PH) V	208 (3PH) V	208 (3PH) V
Input frequency	50/60 Hz +/- 5 Hz (auto sensing)	50/60 Hz +/- 5 Hz (auto sensing)	50/60 Hz +/- 5 Hz (auto sensing)	50/60 Hz +/- 5 Hz (auto sensing)
Input Connection Type	Hard Wire 5-wire (3PH + N + G)	Hard Wire 5-wire (3PH + N + G)	Hard Wire 5-wire (3PH + N + G)	Hard Wire 5-wire (3PH + N + G)
BATTERY				
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	--	--	--	--
PHYSICAL				
Maximum height dimensions	82.00 inches	82.00 inches	82.00 inches	82.00 inches
Maximum width dimensions	48.00 inches	24.00 inches	24.00 inches	24.00 inches
Maximum depth dimensions	35.50 inches	35.50 inches	35.50 inches	35.50 inches
Net weight	895.00 lbs.	1,165.00 lbs.	1,435.00 lbs.	1,705.00 lbs.
Shipping Weight	997.00 lbs.	1,291.00 lbs.	1,585.00 lbs.	1,879.00 lbs.
Shipping Height	91.00 inches	91.00 inches	91.00 inches	91.00 inches
Shipping Width	59.00 inches	29.50 inches	29.50 inches	29.50 inches
Shipping Depth	41.50 inches	41.50 inches	41.50 inches	41.50 inches
ENVIRONMENTAL				
Operating Environment	0 - 40 °C	0 - 40 °C	0 - 40 °C	0 - 40 °C
Operating Relative Humidity	0 - 95 %	0 - 95 %	0 - 95 %	0 - 95 %
Protection Class	NEMA 1	NEMA 1	NEMA 1	NEMA 1
CONFORMANCE				
Approvals	cUL Listed, EN 50091-1, EN 50091-2, EN 50091-3, FCC Part 15 Class A, ISO 14001, ISO 9001, UL 1778, UL 60950	cUL Listed, EN 50091-1, EN 50091-2, FCC Part 15 Class A, ISO 14001, ISO 9001, UL 1778, UL 60950	cUL Recognized, EN 50091-1, EN 50091-2, FCC Part 15 Class A, ISO 14001, ISO 9001, UL 1778, UL 60950	cUL Listed, EN 50091-1, EN 50091-2, FCC Part 15 Class A, ISO 14001, ISO 9001, UL 1778, UL 60950
Standard warranty	2 years parts, optional on-site warranties available, optional extended warranties available	2 years parts, optional on-site warranties available, optional extended warranties available	2 years parts, optional on-site warranties available, optional extended warranties available	2 years parts, optional on-site warranties available, optional extended warranties available

APC's quality system is certified by ISO 9001 standards



For more information call:
Tel: 800 800 4APC - US & Canada
Tel: 401 789 0204 - World wide

APC Corporate
APC North America
132 Fairgrounds Road
West Kingston RI 02892 USA
Call: 800 800 4APC
Fax: 401 789 3710

APC Europe
APC Ireland
Ballybrit Business Park
Galway, Ireland
Call: +35 391 702000
Fax: +35 391 756909

APC Asia Pacific
APC Australia
Level 13, The Denison
65 Berry Street
North Sydney, NSW2060
Call: +61 2 8923 9373

APC Latin America
5301 Blue Lagoon Dr. Suite
#610, Miami FL 33126 USA
Call: 305 266 5005
Fax: 305 266 9695

Visit: www.apc.com
E-mail: apcinfo@apcc.com
Web Support:
support.apcc.com
PowerFax™: 800-347-FAXX

APC
Legendary Reliability®