

Allied Telesis AT-FS202 (AT-FS202-60)

10/100TX Fast Ethernet to 100FX (SC) multimode fiber standalone media and rate converter



Price details:

Price excl. VAT: 189.64 €

Eco fees: 0.04 €

VAT 21 %: 39.83 €

Product details:

Product code: AT-FS202-60

EAN: 5052217063786

Manufacturer: Allied Telesis

PDF generated on: 1 March, 2011



229.51 €

* VAT included

AT-FS200 Series Fast Ethernet bridging media converters are two port, unmanaged and standalone. They convert copper to fiber media, enabling both ports to operate at the same or at different speeds.

Media conversion offers you the ability to:

- Extend network distances by adding fiber only where it is needed.
- Add new devices without replacing costly cable.
- Keep pace with changing technology.
- Integrate high-bandwidth devices into the network.

Main specifications:

Networking

Data transfer rate: 100 Mbit/s

Weight & dimensions

Dimensions W x D x H: 105 x 95 x 25 mm

Weight: 320 g

Energy management

Power consumption: 6 W

Power requirements: 100-120V AC/60Hz, 220-240V AC/50Hz

Technical details

Maximum operating distance: 100000 m

I/O ports: 1x 100TX (RJ-45) 1x 100FX (SC)

Environmental conditions

Operating relative humidity range: 10 - 90 %

Storage temperature range (T-T): -25 - 70 °C

Operating temperature range (T-T): 0 - 40 °C

Storage relative humidity range: 5 - 95 %

Certificates

Safety: UL-Cul, CSA/CSA, NRTL, TUV, CE