

AT-GS950/8POE

8 port Gigabit Fanless PoE WebSmart Switch



AT-GS950/8POE-xx

8 port 10/100/1000T PoE WebSmart switch with 2 SFP combo ports

Performance

Allied Telesis' WebSmart switch integrates the simplicity of unmanaged switches with the performance and reliability of managed switches to provide a cost-effective solution for users to integrate management at the edge of their network. This WebSmart switch provides a network manager some key features using the simple web-based management function such as; port-based VLANs, IEEE 802.1p QoS, port trunking/link aggregation, port mirroring, priority queues and IEEE 802.1x security support. With support of up to 8K MAC addresses, a 1MB packet buffer and a fanless design, the AT-GS950/8POE is an ideal option for integrating management into your network solution.

Power over Ethernet

Capable of providing up to 4 ports of Class 3 (15.4W), the AT-GS950/8POE is ideally suited for those applications using security cameras, wireless access points, IP phones, and other PoE powered devices. The PoE option eliminates the need for power rewiring and minimizes the clutter of power supplies and adapters in awkward places. The silent, fanless operation is perfect for the classroom and other low-noise requirement application.

Value

Never thought you could afford managed switches in your network? Always wanted to provide management functionality at the edge? Now's your chance. Allied Telesis' WebSmart switch truly helps network managers get the most value for their dollar. With industry standard protocols, fiber media support via the SFP's and simple Plug and Play usability right out of the box how can you go wrong implementing this cost-effective solution into your network?

Key Features

Basic features

- Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3z/ab, IEEE 802.3x
- 8 10/100/1000Mbps auto-sensing, auto MDI-X switching port
- 2 individual SFP for combo ports that supports 100/1000Mbps (combo with ports 7 and 8), optical port has the higher priority
- PoE support (full 15.4 W on ports 1-4)
- Support backpressure flow control at half-duplex, IEEE 802.3x flow control at full-duplex
- Head of Line (HoL) blocking prevention
- 19-inch rack-mountable
- Internal power supply
- Standard 1U chassis high
- Fanless design
- 1Mbit (1024 kilobit) on-chip buffer memory

Smart function support

- VLAN ID's available: 4K
- Max VLANs: 200 tagged + 56 port-based
- Web-based configuration interface
- Port-based VLANs
- IEEE 802.1p-based QoS support, four priority queues per port
- IEEE 802.3ad port trunking (four groups)
- Port setting / configuration
- IEEE 802.1D Spanning-Tree, IEEE 802.1w Rapid Spanning-Tree
- SNMP v1, v2
- Storm control
- Jumbo frames, up to 9KB
- Port setting on speed, flow control, and on-off
- Port mirroring
- Dynamic Host Configuration Protocol (DHCP)
- IEEE 802.1x port-based authentication
- Factory reset with hardware push button and software backdoor password
- Configuration backup/restore via TFTP / HTTP
- Password Access Control and restricted IP access list
- Firmware upgradeable via TFTP/HTTP

- RFC 1213 MIB II, RFC 1643 Ethernet Interface MIB, RFC 1493 Bridge MIB, Private Enterprise MIB
- RFC 2131 DHCP client
- IGMP snooping v1 and v2
- RMON (history, statistics, alarms and events)
- ACL's – drop or rate limit based on: source and destination MAC-based, source and destination IP address, protocol, ToS/DSCP, port, VLAN, EtherType

PoE features

- Auto-sensing algorithm - automatically detecting Power over Ethernet terminals and supplying inline power
- LED display of per-port-PoE status supported
- Supports IEEE 802.3af Data Terminal Equipment (DTE)
- RJ-45 wire pairs 4-5, 7-8 for power transmission

AT-GS950/8POE | 8 port Gigabit Fanless PoE WebSmart Switch

Quality and Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesis offers proven reliability and industry recognized quality.

Performance

14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps Ethernet
1,488,000pps for 1000Mbps Ethernet

MAC addresses 8K
VLAN ID's available 4K
Max VLANs 200 tagged + 56 port-based

Packet buffer 1MB

DRAM 32MB
Flash 8MB

Switching capacity 16Gbps
Throughput 11.9Mpps

Power Characteristics

Voltage 90-240V AC
Frequency 50/60Hz
PoE 50V/1.2A, 61.6W for PoE, DPSN-100CP under FAN less condition 5V/6A, 30W for system, ADP-30JP

Interface Connections

10/100/1000T RJ-45
SFP 100TX, 100FX, 1000T, 1000SX or 1000LX

Environmental Specifications

Operating temp. 0°C to 40°C (32°F to 104°F)
Non-operating temp. -25°C to 70°C (-13°F to 158°F)
Operating humidity 5% to 90% non-condensing
Storage humidity 5% to 95% non-condensing

Vibration IEC 68-2-36
Shock IEC 68-2-29
Drop IEC 68-2-32

Technical Specifications

Physical Characteristics

Dimensions 32cm x 23cm x 4.3cm
(W x D x H) 13 x 9.1 x 1.7in

Weight 2.54Kg
5.6lbs

Mounting Ability

All units come with wall / 19" rack-mount brackets

Standards and Compliance

IEEE 802.3	CSMA/CD
IEEE 802.3i	10T
IEEE 802.3u	100TX
IEEE 802.3z	1000SX
IEEE 802.3z/ab	1000T
IEEE 802.3x	Flow control
IEEE 802.1p	Prioritization (four queues)
IEEE 802.1x	Authentication
IEEE 802.1d	Bridging
IEEE 802.3ad	Link aggregation
IEEE 802.1Q	Tagged VLAN
IEEE 802.1d/w	Spanning-Tree
	Rapid Spanning-Tree
IEEE 802.3af	PoE

Electrical/Mechanical Approvals

UL 1950
FCC/EN55022 Class A
VCCI Class A
C-Tick
EN60950 (TUV)
EN55024
CE
CSA / CUL

MTBF

256,000 hours
Bellcore TR332

Ordering Information

AT-GS950/8POE-xx

8 port 10/100/1000T PoE fanless WebSmart switch with 2 SFP combo ports

Where xx = 10 for US power cord
30 for UK power cord
40 for Australian power cord
50 for European power cord

Product Contents

Switch unit
Rack-mount/wall-mount brackets and screws
Power cord
User manual/install guide on CD
Rubber feet

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2009 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000291 Rev.F