

Acer P5205 DLP Projector Specifications

General	Aspect Ratio	4:3 (Native) 16:9
	Brightness (ANSI Lumens)	4000 ANSI Lumens (Normal) 3200 ANSI Lumens (Eco Mode)
	Contrast Ratio	2500:1
	Display Type	DLP
	Resolution (Native / Max)	XGA (1024 x 768) UXGA (1600 x 1200)
	Video Compatibility	NTSC (3.58, 4.43), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
	Projection Lens	F = 2.6 ~ 2.9 f = 16.9 ~ 21.9mm
Size	Dimensions (WxHxD)	11.4in. x 3.9in. x 10.0in. (28.96cm x 9.91cm x 25.4cm)
	Weight	7.2 lbs. (3.27 kg)
Connectivity	Inputs	2 x RGB D-Sub 15pin 1 x Composite 1 x S-Video 1 x HDMI 1 x Stereo Mini Jack 1 x RCA Audio
	Outputs	1 x RGB D-Sub 15pin 1 x Stereo Mini Jack
	Audio	2 x 5W Stereo Speakers
	Control	1 x RS-232 1 x 12V Trigger 1 x RJ-45 LAN Ethernet Port
Operation	Power Supply	100 ~ 240 V / 50 ~ 60 Hz
	Power Consumption	425W (Normal) 1W (Standby)
	Audible Noise	34 dB (Normal) 29 dB (Eco Mode)
Projection Lens	Lamp Type	280W UHP
	Lamp Life	2000 hrs (Normal) 3000 hrs (Eco Mode)
	Projection Distance	3.9ft. ~ 30.2ft. (1.19m ~ 9.2m)
	Projection Mode	Front, Rear, Ceiling
	Projection Screen Size (Diagonal)	30in. ~ 300in. (76.2cm ~ 762cm)
	Throw Ratio	1.51 ~ 1.97:1
	Digital Zoom	2x
	Optical Zoom	1.3
	Vertical Keystone Correction	+/- 40 Degrees
	Brightness Uniformity	90%
Other	H-Sync Range	31 ~ 100 kHz
	V-Sync Range	56 ~ 120 Hz
In The Box	Items	Power Cord VGA Cable Composite Cable Remote Control Batteries Carrying Case User Guide Quick Start Guide Security Card
Warranty	Projector	2 Year Warranty
	Lamp	1 Year Warranty