

Deskstar™ 7K1000

3.5-INCH HARD DISK DRIVES

HITACHI
Inspire the Next

Industry's first terabyte hard disk drive for consumer and commercial computing applications

Highlights

- > Storage capacities up to 1TB
- > Perpendicular magnetic recording technology
- > SATA 3.0Gb/s interface
- > Ramp load design increases shock protection and power savings
- > Thermal monitoring and fly height control enhance reliability
- > Three low-power idle modes boost power efficiency
- > Silent seek acoustics achieve ultra-quiet operation
- > Host/drive authentication for hardware security

Applications

- > Internal and external storage for consumer computers
- > Networked storage servers
- > Extreme gaming machines
- > Video editing arrays



1TB, 750GB | 7200 RPM
Serial ATA 3.0Gb/s

An industry first, the Hitachi Deskstar 7K1000 hard disk drive delivers up to one terabyte of storage capacity for demanding consumer and commercial computing products. It leverages the industry's most reliable perpendicular magnetic recording (PMR) techniques and the latest advancements in silent acoustics, shock protection, and head technology to maximize capacity, performance and field reliability. Best-in-class power management and thermal emissions help manufacturers meet energy compliance targets and extend drive life.

Proven PMR technology

Field-proven in 2.5-in. drives, Hitachi's PMR implementation continues to demonstrate reliability equal to or exceeding conventional longitudinal technology. The Deskstar 7K1000's second-generation PMR head and media technology improves noise characteristics and thermal stability.

Reduced power idle modes

Unique to Hitachi drives, the Deskstar 7K1000 features three advanced low-power idle modes—active, unload and low-power. Together, they reduce power consumption at the drive level up to 20%, optimize non-operational latency and lower drive temperature for cooler system operation.

Outstanding shock resistance and power efficiency

Through a patented ramp load/unload design disk heads (in non-operating modes) are unloaded to a ramp outside the disk where they rest in a low-power 'unload idle' state until activated. In low RPM drives, this can reduce power by up to 50%. Ramp load/ unload provides tangible benefits for the drive and host product. It greatly minimizes the risk of shock damage by eliminating direct contact between the heads and disks. Reduced wear and heat improve overall drive reliability. In the event of power loss to the drive, heads are unloaded using energy extracted from the spinning disks. This patented power-saving feature helps to reduce overall maintenance costs and extends the drive service life.

Another contributor to Deskstar 7K1000's exceptional shock performance and power savings is the use of compact, low-mass femto air-bearing sliders.

Extended field reliability

An integrated thermal sensor monitors operating temperature, enabling the host processor to intelligently adjust airflow as needed for cooling. Sensor integration reduces component cost and increases reliability.

Deskstar 7K1000's thermal fly-height control (TFC) uses an integrated heating element to precisely maintain a constant fly-height throughout read and write operations. This reduces raw soft error rate and, in turn, improves overall data integrity, drive performance and reliability.

Deskstar 7K1000's iridium-manganese-chromium (IrMnCr) read head sensor technology offers better performance and reliability in harsh conditions.

Hitachi Design Studios

Located around the world, Hitachi Design Studios assist customers with all aspects of integrating hard drives into consumer electronic devices. Their services focus on drive selection, evaluation and optimization, integration and design-in consulting, software compatibility assessment, performance profiling, problem analysis and reliability consulting.

Specifications

Model(s)	HDS721075KLA330 HDS721010KLA330	
Interface	Serial ATA3.0Gb/s	
Capacity¹	750GB	1TB
Sector size	512 bytes	
Disks/heads	4/8	5/10
Performance		
Data buffer²	32MB	
Rotational speed	7200 RPM	
Media transfer rate (max)	1070Mb/s	
Interface transfer rate (max)	300Mb/s	
Latency	4.17ms (average, 7200 RPM)	
Seek time³	8.2ms read (typical), 9.2ms write (typical)	
Silent-seek time³	14ms read (typical), 15ms write (typical)	
Reliability		
Error rate (non-recoverable)	1 per 1.0 E15 bits transferred	
Load/unload cycles (at 40°C)	50,000	
Availability⁴ (hrs/day x days/wk)	24x7	
Warranty	3 years	
Power		
Supply	+5 VDC (+/- 5%), +12 VDC (+10% / -8%)	
Start up current (max)	2.0A (+12V), 1.2A (+5V)	
Random read/write (average)	11.5W	12.3W
Silent read/write (average)	9.2W	10.2W
Idle (average)	7.6W	8.4W
Unload idle	5.5W	6.1W
Low RPM idle	3.5W	3.7W
Acoustics (A-weighted sound power)		
Idle	2.9bels (typical)	
Silent seek, Seek	3.0bels (typical), 3.2bels (typical)	
Physical		
Dimensions	H (26.1mm) x W (101.6mm) x D (147mm)	
Weight (max)	700g	
Environmental		
Temperature	5 to 60 °C operating, -40 to 70 °C non-operating	
Relative humidity (non-condensing)	8 to 90% operating, 5 to 95% non-operating	
Shock (half sine wave)	70 G/2 ms pulse operating, 300 G/1 ms pulse non-operating	
Vibration (random) (RMS)	0.67G horizontal, 0.67G vertical operating, 1.04G XYZ non-operating	
RoHS⁵ compliant	yes	

1 GB equals one billion bytes when referring to hard drive capacity; accessible capacity may be less.

2 Buffer capacity includes 270 or less KB used for drive firmware.

3 Does not include command overhead.

4 Intended for low duty cycle, non-mission critical applications in PC, nearline and consumer electronics environments.

Note that customer environments may vary from application to application.

5 RoHS refers to the European Union Directive 2002/95/EC on the restriction of certain hazardous substances in electrical and electronic equipment.

Specific application environments such as temperature and duty cycle will affect the overall reliability rates.

For specific application environment reliability rates, please consult Hitachi technical support.

Hitachi Global Storage Technologies trademarks are intended and authorized for use only in countries and jurisdictions in which Hitachi Global Storage Technologies has obtained the rights to use, market and advertise the brand. Contact Hitachi Global Storage Technologies for additional information. Hitachi Global Storage Technologies shall not be liable to third parties for unauthorized use of this document or unauthorized use of its trademarks.

References in this publication to Hitachi Global Storage Technologies' products, programs or services do not imply that Hitachi Global Storage Technologies intends to make these available in all countries in which it operates.

Product specifications provided are sample specifications and do not constitute a warranty. Information is true as of the date of publication and is subject to change. Actual specifications for unique part numbers may vary. Please visit the Support section of our website, www.hitachigst.com/support, for additional information on product specifications. Photographs may show design models.

Hitachi quality and service

All Hitachi hard drives are designed to the highest quality standards with field-proven components. They are backed by Hitachi's worldwide technical support and integration services, enabling global customers to bring their products to market quickly.

Information and Technical Support

www.hitachigst.com (Main Web site)

www.hitachigst.com/partners (Reseller Web site)

North America

support_usa@hitachigst.com

Toll free: 1 888 426-5214

Direct: 1 507 322-2370

Asia Pacific

support_ap@hitachigst.com / 65 6840 9595

EMEA and UK

support_uk@hitachigst.com / 44 20 7133 0032

Germany

support_uk@hitachigst.com / 49 6929 993601

© 2007 Hitachi Global Storage Technologies

Hitachi Global Storage Technologies
 3403 Yerba Buena Road
 San Jose, CA 95135 USA

Produced in the United States 11/07. Revised 7/09.
 All rights reserved.

Deskstar™ is a trademark of Hitachi Global Storage Technologies.