



HP E6400 cl Series

Data sheet

Product overview

The HP E6400 cl Series consists of 6-port 10-GbE stackables with optional 10-GbE add-on modules. Loaded with full Layer 3 features, the 6400cl series switches offer low-cost 10-GbE for high-performance aggregation of clusters of Gigabit switches. Ideal for consolidating multiple wiring closets, the E6400 cl series offers the highest bandwidth on the market today for Gigabit. The HP E6400 cl Series also provides fiber flexibility to connect remote campuses up to 40 km away.

Key features

- Distribution layer
- Layer 2 to Layer 4 feature set
- High performance
- Low-cost 10-GbE connectivity



Features and benefits

Quality of Service (QoS)

- **Rate limiting:** per-port ingress enforced maximums
- **Layer 4 prioritization:** enables prioritization based on TCP/UDP ports
- **Traffic prioritization (IEEE 802.1p):** allows real-time traffic classification into eight priority levels mapped to eight queues
- **Class of Service (CoS):** sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ

Performance

- **160 Gbps backplane with 119 mpps:** unprecedented bandwidth for low-latency throughput
- **Selectable queuing configurations:** increase performance by selecting the queuing configuration that best meets the requirements of network applications
- **Jumbo frames:** on Gigabit and 10-Gigabit ports, allow high-performance remote backup and disaster-recovery services

Resiliency and high availability

- **Router redundancy (XRRP):** allows groups of two routers to dynamically back each other up to create highly available routed environments
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP) and HP port trunking:** support up to four trunks, each with up to four links (ports) per trunk; trunking across modules is supported
- **IEEE 802.1s Multiple Spanning Tree:** provides high link availability in multiple VLAN environments by allowing multiple spanning trees
- **IEEE 802.1w Rapid Convergence Spanning Tree Protocol:** increases network uptime through faster recovery from failed links
- **Optional redundant power supply:** provides uninterrupted power (provided by HP E600 RPS/EPS)

Manageability

- **sFlow (RFC 3176):** wire-speed traffic accounting and monitoring

- **RMON and XRMON:** provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Stacking capability:** single IP address management for a virtual stack of up to 16 switches, including the 3400cl series

Layer 2 switching

- **HP's switch meshing:** dynamically load-balances across multiple active redundant links to increase available aggregate bandwidth
- **VLAN support and tagging:** supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- **GARP VLAN Registration Protocol (GVRP):** allows automatic learning and dynamic assignment of VLANs
- **IEEE 802.1v protocol VLANs:** isolate select non-IPv4 protocols automatically into their own VLANs

Layer 3 routing

- **Layer 3 IP routing:** provides routing of IP at media speed; supports static routes, RIP, RIPv2, and OSPF

Security

- **Access control lists (ACLs):** provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **Source-port filtering:** allows only specified ports to communicate with each other
- **RADIUS/TACACS+:** eases switch management security administration by using a password authentication server
- **Secure Shell (SSHv2):** encrypts all transmitted data for secure, remote command-line interface (CLI) access over IP networks
- **Secure Sockets Layer (SSL):** encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **IEEE 802.1X and RADIUS network logins:** control port-based access for authentication and accountability
- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator

- **Web-based authentication:** similar to IEEE 802.1X, it provides a browser-based environment to authenticate clients that do not support the IEEE 802.1X supplicant
- **Secure File Transfer Protocol (FTP):** allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of switch configuration file
- **Secure access to manage the 6400cl series:** all access methods—CLI, GUI, or MIB—are securely encrypted through SSHv2, SSL, and/or SNMPv3

Convergence

- **IP multicast snooping and data-driven IGMP:** automatically prevents flooding of IP multicast traffic

Warranty and support

- **Lifetime warranty:** for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)*
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to www.hp.com/networking/warranty for details on the support provided and the period during which support is available
- **Software releases:** refer to www.hp.com/networking/warranty for details on the software releases provided and the period during which software releases are available for your product(s)

*Hardware warranty replacement for as long as you own the product, with next business day advance replacement (available in most countries) with a five-year hardware warranty replacement for the disk drive included with HP AllianceONE Services z1 Module, HP Threat Management Services z1 Module, HP PCM+ Agent with AllianceONE Services z1 Module, and HP E-MSM765 z1 Mobility Controller. For details, refer to the HP Software License, Warranty, and Support booklet at www.hp.com/networking/warranty.

Specifications



HP E6400-6XG cl Switch (J8433A)



HP E6410-6XG cl Switch (J8474A)

Ports	6 CX4 10-GbE ports (IEEE 802.3ak Type 10Gbase-CX4); Duplex: full only Supports a maximum of 8 10-GbE ports, with optional module	6 open 10-GbE X2 transceiver slots Supports a maximum of 8 10-GbE ports, with optional module
Cabling	CX4 ports Maximum distance: • 0.5 m to 15 m using CX4 cable • Up to 300 m using J8439A media converter using MMF	X2 transceiver slots HP ProCurve 10-GbE X2-SC LR Optic Maximum distance: • 9/125 μ m single-mode cable = 2-10 km HP ProCurve 10-GbE X2-SC SR Optic Maximum distance: • 62.5 μ m multimode cable @ 160 MHz/km = 2-26 meters • 62.5 μ m multimode cable @ 200 MHz/km = 2-33 meters • 50 μ m multimode cable @ 400 MHz/km = 2-66 meters • 50 μ m multimode cable @ 500 MHz/km = 2-82 meters • 50 μ m multimode cable @ 2000 MHz/km = 2-300 meters HP ProCurve 10-GbE X2-SC ER Optic Maximum distance: • 30 km (40 km using engineered link) HP ProCurve 10-GbE X2-CX4 Transceiver Maximum distance: • 0.5 m to 15 m using CX4 cable • Up to 300 m using J8439A media converter using MMF
Physical characteristics		
Dimensions	16.9(d) x 17.4(w) x 1.7(h) in. (42.93 x 44.2 x 4.32 cm) (1U height)	16.9(d) x 17.4(w) x 1.7(h) in. (42.93 x 44.2 x 4.32 cm) (1U height)
Weight	12.35 lb. (5.60 kg)	13.56 lb. (6.15 kg)
Memory and processor		
Processor	Motorola PowerPC MPC8245 @ 266 MHz, 16 MB flash, 128 MB SDRAM; packet buffer size: 4 MB	Motorola PowerPC MPC8245 @ 266 MHz, 16 MB flash, 128 MB SDRAM; packet buffer size: 4 MB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
Performance		
Latency	< 11.7 μ s (LIFO 64-byte packets)	< 11.7 μ s (LIFO 64-byte packets)
Throughput	up to 119 million pps (64-byte packets)	up to 119 million pps (64-byte packets)
Routing/Switching capacity	160 Gbps	160 Gbps
MAC address table size	16,000 entries	16,000 entries
Environment		
Operating temperature	32°F to 131°F (0°C to 55°C); 104°F (40°C) when used with SR/LR/ER optics	32°F to 131°F (0°C to 55°C); 104°F (40°C) when used with SR/LR/ER optics
Operating relative humidity	15% to 95% @ 104°F (40°C), non-condensing	15% to 95% @ 104°F (40°C), non-condensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	15% to 95% @ 149°F (65°C), non-condensing	15% to 95% @ 149°F (65°C), non-condensing
Altitude	up to 15,000 ft. (4.6 km)	up to 15,000 ft. (4.6 km)
Acoustic	Power: 55 dB; DIN 45635T.19 per ISO 7779 @ < 77°F (25°C)	Power: 55 dB; DIN 45635T.19 per ISO 7779 @ < 77°F (25°C)
Electrical characteristics		
Maximum heat dissipation	383 BTU/hr (404 kJ/hr), including use of optional cl modules with optics	383 BTU/hr (404 kJ/hr), including use of optional cl modules with optics
Voltage	100-127 / 200-240 VAC	100-127 / 200-240 VAC
Current	3 / 1.5 A	3 / 1.5 A
Maximum power rating	112 W	120 W
Frequency	50 / 60 Hz	50 / 60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950
Emissions	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
Immunity		
EN	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2; 4 kV CD, 8 kV AD	IEC 61000-4-2; 4 kV CD, 8 kV AD
Radiated	IEC 61000-4-3; 3 V/m	IEC 61000-4-3; 3 V/m
EFT/Burst	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)
Surge	IEC 61000-4-5; 1 kV/2 kV AC	IEC 61000-4-5; 1 kV/2 kV AC
Conducted	IEC 61000-4-6; 3 V	IEC 61000-4-6; 3 V
Power frequency magnetic field	IEC 61000-4-8; 1 A/m, 50 or 60 Hz	IEC 61000-4-8; 1 A/m, 50 or 60 Hz
Voltage dips and interruptions	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods

Specifications (continued)

	HP E6400-6XG cl Switch (J8433A)	HP E6410-6XG cl Switch (J8474A)
Harmonics	EN 61000-3-2, IEC 61000-3-2	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	EN 61000-3-3, IEC 61000-3-3
Management	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UA438E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UA439E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UA440E)</p> <p>3-year, 24x7 SW phone support, software updates (UF791E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR940E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR941E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR942E)</p> <p>4-year, 24x7 SW phone support, software updates (UR943E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR944E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR945E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR946E)</p> <p>5-year, 24x7 SW phone support, software updates (UR947E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW344E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW345E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW346E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UA438E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UA439E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UA440E)</p> <p>3-year, 24x7 SW phone support, software updates (UF791E)</p> <p>Installation with minimum configuration, system-based pricing (U4826E)</p> <p>Installation with HP-provided configuration, system-based pricing (U4830E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UR940E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UR941E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR942E)</p> <p>4-year, 24x7 SW phone support, software updates (UR943E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UR944E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UR945E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR946E)</p> <p>5-year, 24x7 SW phone support, software updates (UR947E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW344E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW345E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW346E)</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
Standards and protocols (applies to all products in series)	<p>Device management</p> <p>HTML and telnet management</p> <p>General protocols</p> <p>IEEE 802.1D MAC Bridges</p> <p>IEEE 802.1p Priority</p> <p>IEEE 802.1Q VLANs</p> <p>IEEE 802.1s Multiple Spanning Trees</p> <p>IEEE 802.1v VLAN classification by Protocol and Port</p> <p>IEEE 802.1w Rapid Reconfiguration of Spanning Tree</p> <p>IEEE 802.3ad Link Aggregation Control Protocol (LACP)</p> <p>IEEE 802.3ae 10-Gigabit Ethernet</p> <p>IEEE 802.3ak 10GBASE-CX4</p> <p>IEEE 802.3x Flow Control</p> <p>RFC 768 UDP</p> <p>RFC 783 TFTP Protocol (revision 2)</p> <p>RFC 792 ICMP</p> <p>RFC 793 TCP</p> <p>RFC 826 ARP</p> <p>RFC 854 TELNET</p> <p>RFC 951 BOOTP</p> <p>RFC 1058 RIPv1</p> <p>RFC 1542 BOOTP Extensions</p> <p>RFC 2030 Simple Network Time Protocol (SNTP) v4</p> <p>RFC 2131 DHCP</p> <p>RFC 2453 RIPv2</p> <p>RFC 3046 DHCP Relay Agent Information Option</p> <p>IP multicast</p> <p>RFC 3376 IGMPv3</p> <p>MIBs</p> <p>RFC 1213 MIB II</p> <p>RFC 1493 Bridge MIB</p> <p>RFC 1724 RIPv2 MIB</p> <p>RFC 1850 OSPFv2 MIB</p> <p>RFC 2096 IP Forwarding Table MIB</p> <p>RFC 2618 RADIUS Client MIB</p> <p>RFC 2620 RADIUS Accounting MIB</p> <p>RFC 2665 Ethernet-Like-MIB</p> <p>RFC 2668 802.3 MAU MIB</p> <p>RFC 2674 802.1p and IEEE 802.1Q Bridge MIB</p> <p>RFC 2863 The Interfaces Group MIB</p> <p>Network management</p> <p>IEEE 802.1AB Link Layer Discovery Protocol (LLDP)</p> <p>RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)</p> <p>RFC 3164 BSD syslog Protocol</p> <p>RFC 3176 sFlow</p> <p>SNMPv1/v2c/v3</p> <p>XRMON</p> <p>OSPF</p> <p>RFC 2328 OSPFv2</p> <p>QoS/CoS</p> <p>RFC 2474 DiffServ Precedence, including 8 queues/port</p> <p>RFC 2597 DiffServ Assured Forwarding (AF)</p> <p>RFC 2598 DiffServ Expedited Forwarding (EF)</p> <p>Security</p> <p>IEEE 802.1X Port Based Network Access Control</p> <p>RFC 1492 TACACS+</p> <p>RFC 2138 RADIUS Authentication</p> <p>RFC 2866 RADIUS Accounting</p> <p>Secure Sockets Layer (SSL)</p> <p>SSHv1/SSHv2 Secure Shell</p>	

HP E6400 cl Series accessories

Modules

HP 10GbE Media Flex cl Module (J8435A)

HP 10GbE CX4 Copper cl Module (J8434A)

Transceivers

HP X131 10G X2 SC ER Transceiver (J8438A)

HP X130 CX4 Optical Media Converter (J8439A)

HP X131 10G X2 SC SR Transceiver (J8436A)

HP X131 10G X2 CX4 Transceiver (J8440C)

HP X131 10G X2 SC LR Transceiver (J8437A)

Cables

NEW HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

NEW HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)

NEW HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)

NEW HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)

NEW HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)

NEW HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)

NEW HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

NEW HP 0.5 m PremierFlex OM3+ LC/LC Optical Cable (BK837A)

EPS/RPS

HP E600 Redundant and External Power Supply (J8168A)

To learn more, visit www.hp.com/networking

© Copyright 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA3-0706ENW, Created September 2010

