

Overview

HP Compaq LE1711 17-inch LCD Monitor

Models

Product number: EM886AA

Technical Specifications

Panel	Type	17-inch Active Matrix TFT (thin film transistor)
	Viewable Image Area (diagonal)	17 in (43.2 cm)
	Screen Opening (W x H)	13.3 x 10.6 in (33.9 x 27.1 cm)
	Panel Type	TN
	Aspect Ratio	5:4
	Viewing Angle (typ)*	160 degrees horizontal/160 degrees vertical (10:1 minimum contrast ratio)
	Brightness (typ)*	250 nits (cd/m ²)
	Contrast Ratio (typ)*	1000:1
	Response Rate (typ)*	5 ms
	Pixel Pitch	0.264 mm
	Backlight Lamp Life (to half brightness)	50K hours
	*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.	
On Screen Display (OSD) Controls	Buttons or Switches	3-button OSD (menu, minus, plus); power on/off
	Languages	English, French, German, Spanish, Italian, Dutch, Simplified Chinese (Portuguese and Japanese on regional models)
	User Controls	Image Control (auto, horizontal, vertical, sharpness), Color Temperature (6500k, 9300k, Custom, sRGB), Brightness, Contrast, Clock, Clock Phase, Monitor Management (power saver, sleep, power on recall, power on status, DDC/CI support, bezel power LED), Factory Reset
Signal Interface/Performance	Horizontal Frequency	24 to 83 kHz
	Vertical Frequency	50 to 76 Hz
	Native Resolution	1280 x 1024 @ 60 Hz (recommended) (SXGA)
	Maximum Resolution	1280 x 1024 @ 60 Hz (recommended) (SXGA)

QuickSpecs

HP Compaq LE1711 17-inch LCD Monitor

Video Input	Preset VESA Graphic Modes (non-interlaced)	1280 x 1024 @ 60 Hz 1280 x 960 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 720 @ 60 Hz 1024 x 768 @ 60 Hz 800 x 600 @ 60 Hz 720 x 400 @ 70 Hz 640 x 480 @ 60 Hz
	Maximum Pixel Clock Speed	140 MHz
	User Programmable Modes	Yes, 8
	Anti-Glare	Yes
	Anti-Static	Yes
	Default Color Temperature	6500 degrees Kelvin
	Plug and Play	Yes
	Input Signal	15 pin D-sub (Analog VGA)
	Input Impedance	75 ohms (2 % value change allowed)
	Sync Input	TTL separate synch
Power	Video Cable	Detachable 15-pin D-sub mini connector
	Video Cable Length	70.8 in (1.8 m)
	Input Voltage	100- 240 VAC
	Nominal Current	< 0.50 Ampere
	Frequency	50 / 60 Hz
	Maximum	< 28 watts
	Typical	24 watts
Mechanical	Power Saving	< 2 watts
	Power Cable Length	74.8 in (1.9 m); detachable
	Dimensions (H x W x D)	Unpacked w/ stand 15.2 x 14.8 x 8.1 in (38.6 x 37.7 x 20.6cm)
		Display Head only 12.4 x 14.8 x 2.4 in (31.6 x 37.7 x 5.7 cm)
		Packaged 4.8 x 17.6 x 18.6 in (12.1 x 44.8 x 47.2 cm)
	Weight	Head only 7.5 lb (3.4 kg)
		Unpacked 8.6 lb (3.9 kg)
		Packaged 11.2 lb (5.1 kg)
	Tilt Range	-5 to +25 degrees vertical tilt
	Swivel Range	None
	Height Adjustable	No
	Pivot Rotation	No

QuickSpecs

HP Compaq LE1711 17-inch LCD Monitor

Environmental	Base and Stand	Detachable		
	Temperature – Operating	41° to 95° F (5° to 35° C) non-condensing		
	Temperature – Non-operating	-4° to 140° F (-20° to 60° C)		
	Humidity – Operating	20% to 80% non-condensing		
	Humidity – Non-operating	5% to 90%		
	Altitude – Operating	0 to 16,404 ft (0 to 5,000 m)		
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,192 m)		
Environmental Data	Eco-Label Certifications and Declarations	<p>This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:</p> <ul style="list-style-type: none"> • ENERGY STAR® • IT ECO declaration • TCO 5.0 • CECP • EPEAT™ Silver 		
	Energy Consumption(in accordance with ENERGY STAR® test method)	115VAC, 60 Hz	230VAC, 50 Hz	100VAC, 60 Hz
	Normal Operation	31.6W	30.9W	29.8W
	Sleep	0.78W	0.86 W	0.75W
	Off	0.77W	0.87W	0.75W
	Heat Dissipation*	115VAC, 60 Hz	230VAC, 50 Hz	100VAC, 60 Hz
	Normal Operation	108 BTU/hr	106 BTU/hr	102 BTU/hr
	Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
	Off	3 BTU/hr	3 BTU/hr	3 BTU/hr
	*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.			
	Ergonomics	The monitor meets the ergonomic requirement of EN-ISO 13406-2 for flat panel displays.		

Additional Information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) Directive, 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive, 2002/96/EC.

This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).

This product is in compliance with the IEEE 1680 (EPEAT) standard at the Silver level, see www.epeat.net.

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

Display meets the requirement for low frequency electromagnetic fields per TCO and prEN50279 A/B/C.

This product contains 0% recycled materials (by wt.)

This product is 96.2% recyclable when properly disposed of at end of life.

External:

- Paper / Cardboard 774 g
- Polyethylene low density 25 g

Internal:

- EPS (Expanded Polystyrene) 219 g

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at :

www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde

Packaging

- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: www.hp.com/recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment: Global Citizenship Report

www.hp.com/hpinfo/globalcitizenship/gcreport/index.html

Eco-label certifications

www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html

ISO 14001 certificates:

www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html

Options

HP LCD Speaker Bar – Part number EE418AA	Powered directly by the monitor or PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and an external jack for headphones. Sold separately. For more information, refer to the product's QuickSpec.
HP LCD Monitor Quick Release – Part number EM870AA¹	An easy-to-use, VESA-compliant, flat panel monitor mounting solution that allows you to quickly and securely attach a flat panel monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpec document.
HP Integrated Work Center Stand – Part number GN783AA	Allows mounting of a 17- or 19-inch HP LCD monitor and an HP Compaq dc7800 or dc7900 Ultra-slim Desktop PC or select HP thin clients on a single stand for the convenience of an "all-in-one" form factor. Sold separately. For more information, refer to this product's QuickSpec document.

Other

HP Security Lock—Part number PC766A	Combines aircraft-grade steel and Kevlar fiber to securely lock down your monitor and help prevent theft.
Accessories Included	Detachable VGA cable, detachable AC power cord, documentation kit, and user CD.
Software	<p>HP Display LiteSaver feature allows you to schedule Sleep mode at preset times to help protect the monitor against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.</p> <p>HP Display Assistant is a software utility that allows monitor adjustment, theft deterrence, and color calibration using the Display Data Channel Command Interface (DDC/CI) protocol of the connected PC.</p>
User Guide Languages	English, Brazilian Portuguese, French, LA Spanish, Korean, Simplified Chinese, Traditional Chinese, Japanese, Danish, Dutch, Finnish, German, Italian, Norwegian, Swedish, Greek, Polish, Russian, Slovenian, Turkish
Warranty Languages	<p>Americas English, Canadian French</p> <p>LA Spanish, Brazilian Portuguese</p> <p>EMEA English, Danish, Dutch, Finnish, European French, German, Italian, Norwegian, Castilian Spanish, Swedish</p> <p>Asia/Pacific English, Bahasa, S. Chinese, T. Chinese, Korean, Japanese, Chinese</p>
Color	Black/Silver

¹ The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) depending upon the mounting configuration used. Please note this is a total weight limit for all devices mounted, i.e. the combined weight of the monitor and a second device such as the HP Thin Client cannot exceed 24 pounds. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-ready	Yes
Certification and Compliance	ISO 9241-307 pixel defect guidelines, CISPR, VCCI, CSA (Canada), ACA (Australia), TUV and GS Mark (German ergonomic), BSMI (Taiwan), CCC (China), MIC (South Korea), NOM (Mexico), Eastern European approvals, CE Marking, FCC approval, ENERGY STAR® qualified, TCO 5.0 Displays (emissions, ergonomics, environment), Microsoft® Windows® certified (Microsoft Windows 2000, Microsoft Windows XP, and Windows Vista®), GOST (Russia), SASO (Saudi Arabia), EPEAT® Silver	
Compatibility	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.	
Service and Warranty	Three years parts, labor, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement options may include second business day on-site service, or next business day direct replacement, at HP's sole discretion. ² With direct replacement, HP will ship a replacement display product directly to you. Using the prepaid shipping labels provided, return your failed display to HP in the same packaging as the replacement. Certain restrictions and exclusions apply. For details see your product warranty or contact HP Customer Support.	

© 2009 Hewlett-Packard Development Company, L.P.

Microsoft, Windows, and Windows Vista are trademarks of the Microsoft group of companies.

ENERGY STAR is a US registered mark of the United States Environmental Protection Agency.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided as is without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

² HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at www.hp.com/go/lookuptool. Additional HP Care Pack Services information by product is available at www.hp.com/hps/carepack. Service levels and response times for HP Care Packs may vary depending on your geographic location.