

Reduce cost, improve service and manage risk with exceptional power-optimized performance, virtualization and management



IBM System x3650 M2



Highlights

- ***Reduce cost with an energy-smart design that provides optimal computing performance per watt***
- ***Improve service with a flexible design that is easy to deploy, integrate and manage***
- ***Manage risk with resilient architectures and virtualized environments***

Energy-efficient profile

The IBM System x3650 M2 offers robust, proven technology and a flexible, energy-smart design. Delivering quad-core computing on Intel® Xeon® 5500 Series processors with QuickPath Interconnect technology, this server delivers significant performance improvement per watt compared to previous generation servers by integrating low-wattage components for an energy-smart thermal profile.

Powerful systems management

The x3650 M2 offers feature-rich management capabilities from power management to proactive hardware monitoring. The Integrated Management Module (IMM)

increases server availability by continuously monitoring your system and notifying you of potential system failures or changes. The Virtual Media key option provides remote presence capabilities without taking up a slot on the planar, while IBM Systems Director Active Energy Manager™ delivers advanced power monitoring and notification.

Designed for virtualization

Designed to provide leadership virtualization, the x3650 M2 supports the VMware ESXi 3.5 embedded hypervisor, the industry-leading solution for virtualization. In addition, the x3650 M2 provides exceptional memory per core, enabling you to implement virtualization efficiently and cost-effectively.

Select configurations of the x3650 M2 are part of the IBM Express Advantage™ Portfolio, designed to meet the needs of midsized businesses. Easy to manage, Express™ models/configurations vary by country.



IBM System x3650 M2 at a glance

Form factor/height	2U rack
Processor (max)	Up to 2 quad-core Intel Xeon 5500 Series with Intel QuickPath Interconnect (QPI) technology, up to 2.93 GHz and up to 1333 MHz front-side bus
Number of processors (std/max)	1/2
Cache (max)	Up to 8 MB
Memory¹ (max)	1 GB, 2 GB, 4 GB or 8 GB DDR-3 RDIMMs with 16 slots up to 128 GB maximum memory
Expansion slots (I/O)	4 PCI-Express (4x8) Gen 2 slots: 2x8 full-length, full-height; 1x8 half-length, full-height; 1x8 low-profile. 4x8 are convertible to 2x16 via optional risers. Also, 2x PCI-X via optional risers
Disk bays (total/hot-swap)	Up to twelve 2.5" hot-swap Serial Attached SCSI (SAS)/Serial ATA (SATA) HDDs or solid state drives (SSDs)
Maximum internal storage^{1,2}	Up to 6.0 TB hot-swap SAS or up to 6.0 TB hot-swap SATA or up to 600 GB hot-swap SSD storage
Network interface	Integrated 2 ports, plus 2 ports optional Gigabit Ethernet
Power supply (std/max)	1/2; 675 W each
Hot-swap components	Power supplies, fan modules, disks
RAID support	Hardware RAID-0, -1, -1E or RAID-0, -1, -10, -5, -50 (with additional option -6, -60) model dependent
Systems management	IBM IMM with Virtual Media Key for optional remote presence enablement, Predictive Failure Analysis, Integrated Service Processor, Diagnostic LEDs, light path diagnostics panel, Automatic Server Restart, IBM Systems Director and IBM Systems Director Active Energy Manager, IBM ServerGuide
Operating systems supported	Microsoft® Windows Server 2003 and 2008, Red Hat Enterprise Linux®, SUSE Linux Enterprise Server and VMware ESXi 3.5 embedded hypervisor
Limited warranty³	3-year customer replaceable unit and onsite limited warranty

For more information

World Wide Web

U.S. ibm.com/systems/x
Canada ibm.com/ca/en/systems/x

© Copyright IBM Corporation 2009

September 2009
All Rights Reserved

This publication could include technical inaccuracies or photographic or typographical errors. This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. Consult your local IBM business contact for information on the products or services available in your area.

IBM, the IBM logo, ibm.com and System x are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml.

Intel and Xeon are registered trademarks of Intel Corporation or its subsidiaries in the States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Microsoft is a trademark of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.

¹ Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest capacity supported drives available. When referring to variable speed CD-ROMs, CD-Rs, CD-RWs and DVDs, actual playback speed will vary and is often less than the maximum possible.

² GB and TB = 1,000,000,000 and 1,000,000,000,000 bytes, respectively, when referring to storage capacity. Accessible capacity is less.

³ IBM hardware products are made from new parts, or new and serviceable used parts. Regardless, our warranty terms apply. For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services, including those designated as ServerProven®.



Recyclable, please recycle.