



Compar, Inc.
10301 Yellow Circle Drive

Minnetonka, MN 55343-9101
952.945.0300
<http://www.comparinc.com>



Lenovo ThinkVision L2250p

LCD display - TFT - 22" - widescreen - 1680 x 1050 / 75 Hz - 250 cd/m2 - 1000:1 - 5 ms - 0.282 mm DVI-D, VGA - business black -

Manufacturer: Lenovo

Part #: 2572HB6

Printed On: Nov 6, 2009 8:20 AM CST

Product Description

The ThinkVision L2250p wide delivers the perfect balance between productivity, environmental responsibility, and value. The L2250p wide is 29% more energy-efficient than the latest Energy Star 5.0 standards. 25% of the total weight of all plastics in the product consists of post-consumer content plastic resins. With arsenic-free glass, the L2250p wide enables you to be environmentally friendly without compromising performance. The wide format offers users improved productivity with a larger display area and more comfortable viewing, especially for data crunchers. This monitor is the perfect choice for users seeking improved office applications productivity and user comfort. As defined by EPEAT verification criteria for calculation of post-consumer recycled content.

Main Specifications	
Product Description	Lenovo ThinkVision L2250p - LCD display - TFT - 22"
Device Type	LCD display / TFT active matrix
Color	Business black
Dimensions (WxDxH)	19.9 in x 6.1 in x 15.7 in
Weight	11.5 lbs
Diagonal Size	22" - widescreen
Viewable Size	22"
Dot Pitch / Pixel Pitch	0.282 mm
Max Resolution	1680 x 1050 / 75 Hz
Display Positions Adjustments	Height, tilt
Color Support	24-bit (16.7 million colors)
Image Aspect Ratio	16:10
Response Time	5 ms
Image Brightness	250 cd/m2
Image Contrast Ratio	1000:1
Digital Video Standard	Digital Visual Interface (DVI)
Signal Input	DVI-D, VGA
Microsoft Certification	Certified for Windows Vista
Compliant Standards	FCC Class B certified, CE, MPR II, CSA, UL, TUV, C-Tick, BSMI, VCCI Class B ITE, cUL, GS, NEMKO, NOM, SABS, SASO, TUV S, VESA DPMS, IEC 60950, CCC, IC, PSB, RoHS, TCO Displays 5.0, ISO 9241-307, WEEE
Power	AC 120/230 V (50/60 Hz)
Power Consumption Operational	21 Watt

Environmental Standards	EPA Energy Star
Manufacturer Warranty	3 years warranty
General	
Display Type	LCD display / TFT active matrix
TFT Technology	TN
Width	19.9 in
Depth	6.1 in
Height	15.7 in
Weight	11.5 lbs
Enclosure Color	Business black
Display	
Diagonal Size	22" - widescreen
Viewable Size	22"
Dot Pitch / Pixel Pitch	0.282 mm
Max Resolution	1680 x 1050 / 75 Hz
Color Support	24-bit (16.7 million colors)
Max Sync Rate (V x H)	75 Hz x 83 kHz
Video Bandwidth	205 MHz
Response Time	5 ms
Controls / Adjustments	Brightness, contrast, H/V position, input select
Display Positions Adjustments	Height, tilt
OSD Languages	Chinese (simplified), English, German, French, Italian, Russian, Spanish, Japanese
Display Screen Coating	Anti-glare, anti-reflective
Tilt Angle	23
Signal Input	DVI-D, VGA
Features	HDCP, 72% color gamut
Image	
Image Aspect Ratio	16:10
Image Brightness	250 cd/m2
Image Contrast Ratio	1000:1
Image Max H-View Angle	176
Image Max V-View Angle	170
Video Input	
Analog Video Signal	RGB
Digital Video Standard	Digital Visual Interface (DVI)
Expansion / Connectivity	
Interfaces	1 x DVI-D - 24 pin digital DVI 1 x VGA - 15 pin HD D-Sub (HD-15)
Miscellaneous	
Cables Included	1 x DVI cable - 6 ft 1 x VGA cable - 6 ft
Mounting Kit	Optional
Flat Panel Mount Interface	100 x 100 mm
Features	Security lock slot (cable lock sold separately)
Certified for Windows Vista	Certified for Windows Vista software and devices have undergone compatibility tests for ease-of-use, better performance and enhanced security.
Compliant Standards	FCC Class B certified, CE, MPR II, CSA, UL, TUV, C-Tick, BSMI, VCCI Class B ITE, cUL, GS, NEMKO, NOM, SABS, SASO, TUV S, VESA DPMS, IEC 60950, CCC, IC, PSB, RoHS, TCO Displays 5.0, ISO 9241-307, WEEE
Power	

Form Factor	Internal
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	21 Watt
Power Consumption Stand by / Sleep	1 Watt
Software / System Requirements	
OS Required	Microsoft DOS, Microsoft Windows XP, Microsoft Windows 7, Microsoft Windows Vista
Environmental Standards	
EPA Energy Star Compliant	Yes
Manufacturer Warranty	
Service & Support	3 years warranty
Service & Support Details	Limited warranty - replacement - 3 years - carry-in
Environmental Parameters	
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 80%