

VA926g

48cm/19" LED DISPLAY



> 100,000:1 Dynamic Contrast Ratio

Provides for darker black levels and better overall front-of-screen performance.

> 5ms video response delivers superior picture clarity

> 1280 x 1024 native resolution

Incredible image detail for sharp text and graphics.

> OptiSync® multiple analogue/digital inputs

Multi-mode input technology supports both digital (DVI-HDCP) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.

> Slim-bezel design

An ultra-thin bezel lets you see more without taking up valuable-desktop real estate.

> OSD/power lock secures your settings

Prevents changes to monitor settings and maintains an optimised image.

> OnView controls for superior screen adjustability

Screen adjustments are precisely made via an easy-to-use on-screen menu.

> TCO 5.0 and ENERGY STAR qualified

Model Name	VA926g	
LCD	Size	48cm/19" TN colour TFT active matrix SXGA LCD
	Optimum Resolution	1280×1024
	Brightness (cd/m²)	250 (Typical)
	Contrast Ratio (Typical)	1000:1
	Dynamic Contrast Ratio	100,000:1
	Viewing Angle (CR ≥ 10 / CR ≥ 5)	170° horizontal, 160° vertical
	Response Time (ms)	5 (typical)
	Pixel Pitch (H×V)	0.294 × 0.294 (mm)
	Panel Surface	Anti-Glare
	Light Source (Hours)	40,000 (Typ.)
	Colour Support (Millions of colours)	16.7 Millions
INPUT	Analogue	RGB Analogue (75 ohms, 0.7 / 1.0 Vp-p)
	Digital	DVI-D(TMDs, 100 ohm)
	Sync	H/V Sperate(TTL)
	Frequency (Fh / Fv)	24-82kHz / 50-75Hz
COMPATIBILITY	PC	VGA up to 1280×1024 Non Interlaced
	Mac	1280×1024 Non Interlaced
CONNECTOR	Analogue	15-pin mini D-Sub
	Digital	24-pin DVI-D
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100-240V (Universal); 50/60Hz(auto switch), internal power supply
	Consumption (W)	25 W (typical)
	Start Mode(W)	<1W
CONTROLS	Basic	Power, menu [1], up, down, select [2]
	OnView / OSD	Auto image adjust, contrast, brightness, ViewMatchcolour adjust (sRGB, 9300K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), auto white balance, OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0 - 40 (°C) / 32 - 104 (°F)
	Humidity (Non condensed)	20 - 90 (%)
DIMENSIONS (WxHxD mm)	Physical (w/ stand)	412(W) x 435(H) x 195(D)mm
WEIGHT	Net (w/ stand)	4.1 kg (9.02lbs)
REGULATIONS		TCO 5.0, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CE, CB, GOST-R, Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, NOM, SASO, ENERGY, ENERGY STAR, C-Tick, KTL/MIC, BSMI, PSB, MPR II, TÜV-S, CCC, VCCI, WEEE, RoHS
WALL MOUNT (mm)	VESA® Mount Compliant	100 × 100