

VP2650wb

**26" (25.5" VIEWABLE)
PROFESSIONAL LCD**

**WITH 110% NTSC
OPTICOLOR™ TECHNOLOGY**

Professional-grade color and performance.

The 26" (25.5" viewable) VP2650wb widescreen LCD features OptiColor™ technology with 110% NTSC color capability for BETTER COLOR ACCURACY and more detailed images in any viewing environment. Creative and business professionals will enjoy the EXPANSIVE COLOR GAMUT available in the VP2650wb.

Complementing the intense color range are 3ms video response, 4000:1 Dynamic Contrast Ratio, and 1920x1200 native resolution to display true HD content and full-motion images. This display also features PerfectSuite™ Plus software for hassle-free set up and maintenance. With ADVANCED ERGONOMIC ADJUSTMENTS and an ultra-thin bezel for multiple display configurations, the VP2650wb is the ideal choice for graphics professionals, movie production and serious gamers.



PRECISE, VIBRANT COLOR

- > **OptiColor™ technology**
Delivers 110% color saturation for richer, more precise colors. Enjoy more intense colors in your graphics, photos and documents.
- > **ClearMotiv® 3ms video response**
Ultra-fast video response enables digital, HD broadcast-quality video.
- > **4000:1 dynamic contrast ratio**
Provides for darker black levels and better overall front-of-screen performance.
- > **Pivot, height and wall-mount versatility**
VESA® wall-mount interface and detachable base for ergonomic flexibility with pivot,* height, tilt and 120° swivel adjustments.
- > **PerfectSuite™ Plus control software**
Professional-grade LCD control software featuring color calibration, asset management, theft deterrence, and auto screen rotation.*
- > **Full 25.5" viewable widescreen with 1920x1200 resolution**
- > **Multiple analog/digital inputs and integrated USB hub expand your connectivity**
- > **Certified for Windows Vista®**

**1920x1200
SUPER HD**

**4000:1
Dynamic Contrast Ratio**

**4 USB
PORTS**

OptiColor™



ViewSonic®
See the difference® 

VP2650wb



26" (25.5" VIEWABLE) PROFESSIONAL LCD WITH 110% NTSC OPTICOLOR™ TECHNOLOGY



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
Riverside House
7th Floor
2a Southwark Bridge Road
London, SE1 9HA
United Kingdom
Tel: +44 (0) 207 921 2200
Fax: +44 (0) 207 921 2201

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47677 Willich
Germany
Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France
Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA
Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux	Tel: +32 (0)56 85 26 27
ViewSonic Denmark	Tel: +45 70 22 11 71
ViewSonic Finland	Tel: +358 (0)20 7120 860
ViewSonic MEA	Tel: +971 (0) 4 88 11 871
ViewSonic Netherlands	Tel: +31 (0)20 491 9254
ViewSonic Norway	Tel: +47 (0) 22 88 17 60
ViewSonic Spain	Tel: +34 (0) 91 63 05 339
ViewSonic Sweden	Tel: +46 (0) 8 50 71 30 00

LCD	Type	26" (25.5" viewable) Color TFT active matrix LCD
	Display Area	550x344mm
		21.7" horizontal x 13.5" vertical; 25.5" diagonal
	Optimum Resolution	1920x1200
	Contrast Ratio	1000:1 static (typ), 4000:1 dynamic
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 10:1 170° horizontal, 170° vertical @ contrast ratio > 5:1
	Response Time	3ms gray-to-gray (avg); 5ms black-white-black (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	400 cd/m ² (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7/1.0 Vp-p) / DVI (HDCP)
	Frequency	F _H : 24~92kHz, F _V : 50~85Hz
	Sync	H/V separated (TTL), composite, sync-on-green
COMPATIBILITY	PC	VGA up to 1920x1200 non-interlaced
	Mac ^{®**}	G3/G4/G5 up to 1920x1200; PerfectSuite™ Plus and pivot function not supported by ViewSonic.
CONNECTOR	Analog/Digital	15-pin mini D-sub / DVI-D
	USB	V2.0, 1-up/4-down
	Power	Internal power; 3-pin AC plug (CEE22)
POWER	Voltage	AC 100~240V, 50~60Hz (auto switch)
	Consumption	110W (typ)
CONTROLS	Basic	Power, 2, up, down, 1
	OnView [®]	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch [®] color adjust (sRGB, 9300K, 7500K, 6500K-default, 5000K, user color-RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness, dynamic contrast, aspect ratio, display mode), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background, OSD pivot), memory recall
ERGONOMICS		Height adjustment range 4.7", tilt, swivel range 120°, pivot
OPERATING	Temperature	32~104°F (0~40°C)
CONDITIONS	Humidity	10~90% (non-condensing)
DIMENSIONS	Physical with stand	23.4" x 18.4" x 15.3" (595mm x 468mm x 388mm)
	Physical without stand	23.4" x 15.3" x 3.9" (595mm x 389mm x 100mm)
(W x H x D)		
WEIGHT	Net with stand	25.4 lb. (11.5 kg)
	Net without stand	20.0 lb. (9.1 kg)
	Gross with stand	31.7 lb. (14.4 kg)
REGULATIONS		UL, cUL, FCC-B (ICES), CB, CE, TCO'03, ICES-003B, ISO 13406-2, TUV/GS, TUV ERGO (covers ISO 13406-2 & MPR II), TUV-S, NOM, GOST-R, HYGIENIC, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS, EPEAT-Silver
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
POWER MANAGEMENT		Meets TCO'03 standards
PACKAGE CONTENTS		LCD display, power cable, VGA cable, DVI cable, USB cable, Quick Start Guide, ViewSonic Wizard CD, PerfectSuite™ Plus CD
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/

*PerfectSuite™ and pivot function not supported by ViewSonic on Apple computers. **Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [13771-00B-06/08/VP2650wb-1